

COMPETITIVE FEATURES, BEST PRICED 4 IPS THERMAL TRANSFER PRINTER IN THE WORLD.



TTP-244 DESKTOP THERMAL TRANSFER BAR CODE PRINTER

The new TSC™ TTP-244 thermal transfer bar code printer is a robust label printer. It is designed to provide labeling solutions for customer who simply needs to print labels and tags at the lowest cost.

It re-defines low volume desktop bar code printing. With the largest media/ribbon capacities, fast print speed, and large memory capacity in its class, the TTP-244 outperforms the competition easily. These virtually trouble free units feature a standard two-year warranty. Once you plug it in, you won't have to worry about it.

The TTP-244 is based on the best selling TTP-243 platform, features such as legendary Dual-Motor design, and industrial standard media capacity. With its small, compact footprint, it is perfect for a variety of label and tag printing applications. The TTP-244 can print a wide variety of labels ranging from low volume shipping labels to compliance and general purpose product identification labels and tags.

Other applications include automobile service shops, walk-in shipping and mail centers, and inventory control for stock rooms. And with PDF417 and MaxiCode two dimensional bar code capabilities, the TTP-244 can print complex transportation formats.

The TTP-244 offers the following features:

- ▶ 2 MB DRAM, 2MB FLASH memory
- ▶ Dual-Motor gear driven design
- ▶ 300 meter ribbon supply on 1" core (coated side out)
- ▶ 4.3" OD internal media supply, optional 8.4" OD external media holder
- ▶ 4 inches per second print speed
- ▶ Serial & USB interfaces
- ▶ Free bundled labeling software



Value . Performance . Support

TTP-244

DESKTOP THERMAL TRANSFER BAR CODE PRINTER

TSC
Connecting Your Thermal Printing Needs.™

SPECIFICATIONS

Printer model	TTP-244
Resolution	203 DPI
Printing method	Thermal Transfer
Print speed	Up to 4 ips
Max. print width	104 mm (4.09")
Max. print length	1016 mm (40")
Enclosure	ABS plastic
Physical dimension	288 mm (L) x 232 mm (W) x 156 mm (H) 11.34" (L) x 9.13" (W) x 6.14" (H)
Ribbon capacity	300 m (984 ft.), 1" core, Max. OD 67 mm
Label roll capacity	109.2 mm (4.3") OD
Processor	32-bit RISC CPU
Memory	● 2MB Flash memory ● 2MB DRAM
Interface	● Standard RS-232 (max. 19,200 bps) ● USB 1.1 or Centronics (factory option)
Power	AC input: 100-240V universal switching power supply DC output: 24V 2A
Operation switch, button	● One power switch ● Feed button and Pause button
Sensors	● Transmissive sensor ● Reflective sensor ● Ribbon end sensor
Internal font	8 alpha-numeric bitmap fonts, one true type font-CG triumvirate bold condensed
Code Page	● Codepage 850 (Latin 1) ● Codepage 852 (Latin 2) ● Codepage 860 (Portuguese) ● Codepage 863 (French Canadian) ● Codepage 865 (Nordic) ● Codepage 857 (Turkish) ● Codepage 861 (Iceland) ● Codepage 1252 (Latin 1) ● Codepage 1250 (Latin 2) ● Codepage 1254 (Turkish) ● Latin-1 (ISO-8859-1: Western European) ● Latin-2 (ISO-8859-2: Central European) ● Latin-9 (ISO-8859-9: Turkish)
Bar code	1D bar code Code 39, Code 39C, Code 93, Code128UCC, Code128 subsets A,B,C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, ITF 14, EAN 14 2D bar code PDF-417, Maxicode, DataMatrix, QR code
Font & barcode rotation	0, 90, 180, 270 degrees
Printer language	● TSPL2 ● TSPL-EZ
Media type	Continuous, die-cut, Fan-fold, black mark, tag
Media wound type	Outside wound
Media width	25.4~114mm (1.0" ~ 4.4")
Media thickness	0.06~0.25 mm (2.36~9.84 mil)
Media core diameter	25.4~76.2 mm (1"~3")
Label length	10 mm (0.4")~1016 mm (40")
Environment condition	Operation: 5~40°C(41°F~104°F), 25~85% non-condensing Storage: -40~60°C(-40°F~140°F), 10~90% non-condensing
Safety regulation	FCC Class A, CE Class A, C-Tick Class A, BSMI Class A, TUV/GS, CCC
Accessories	● BarTender UltraLite Edition Labeling software CD disk ● Quick start guide ● External auto switching power supply ● Power cord ● Label Spindle, fixing tab x2 ● Ribbon spindle x2 ● Ribbon rewind spindle paper core
Limited warranty	● Printer: 2 years ● TPH: 1 million inches or 12 months which comes first since delivery from TSC ● Platen: 50 km
Factory option	● On board secondary Flash 2MB ● Centronics Parallel port (SPP mode)
User option	● Keyboard display unit (KU-007 Plus and KP-200) ● External Ethernet print server ● External wireless (802.11b/g) print server ● External roll mount, media OD 214 mm (8.4") with 1" or 3" core ● 3" core label spindle ● Contact CCD bar code scanner ● Long range linear image bar code scanner ● Battery pack



Authorized Distributor

Pennueng Holding Co.,Ltd.

Tel : +66 2 216 8188 Fax : +66 2 215 2067

sales@pen1.biz , www.pen1.biz